

REAL GAS PROPERTIES FOR HUMID AIR. THERMODYNAMIC PROPERTIES

Liviu COSTIUC

University "Transilvania" of Braşov, ROMANIA

Bd. Eroilor, Nr.29, cod 500036, Braşov, tel.0268 470017, fax: 0268 410525

e-mail: lcostiuc@unitbv.ro

ABSTRACT

The modeling of the components that are used in modeling of refrigeration, HVAC equipment and plant require the knowledge of thermodynamic and transport properties of humid air. In the last few years, the development of control techniques for equipment and plants, the increasing of the computing power of microcontrollers used, requires a model conceived for design purposes at start, and air humid properties must be calculated for real fluids. Because the humid air or water are used in a cyclic process, with mixing, drying or humidifying stages, the thermodynamic and transport properties are required for the liquid, the vapour phase, and also for two-phase liquid-vapor region. Water properties are mostly necessary for the liquid phase, although the frost and ice properties may as well be required when the source fluid is atmospheric air. This paper describes the equations necessary for the calculation of the thermodynamic and transport properties of humid air considered as a mixture of real gases, and also calculations for dew-point and wet-bulb temperature.

REFERENCES

- [1] CONDE M. -Thermophysical Properties of Humid Air, M.Conde Engineering, Zurich. 2002,
- [2] REID R.C., PRAUSNITZ J.M., POLING B.E. -The Properties of Gases and Liquids, McGraw-Hill, 1984
- [3] BLACK, C. -Importance of Thermophysical Data in Process Simulation, Int. J. Thermophysics, 7(4), 1986
- [4] CHEUNG, H. L., A. BROMLEY, C. R. WILKE -Thermal Conductivity of Gas Mixtures, AIChE Journal, 8(2), 1962.
- [5] FLIK, M. I., M. R. CONDE PSYCHI - A Pascal Procedure for the Calculation of the Psychrometric Properties of Moist Air, Internal Report, Energy Systems Laboratory, ETH Zurich, 1986.
- [6] GOFF, J. A. -Standardization of Thermodynamic Properties of Moist Air, ASHVE Transactions, 1949.
- [7] HYLAND, R. W., A. WEXLER -Formulations for the Thermodynamic Properties of Dry Air from 173.15 K to 473.15 K, and of Saturated Moist Air from 173.15 K to 372.15 K, at Pressures up to 5 Mpa, ASHRAE Trans., 89/2, 1983.
- [8] HYLAND, R. W., A. WEXLER -Formulations of the Thermodynamic Properties of the Saturated Phases of H₂O from 173.15 K to 473.15 K, ASHRAE Trans., 89/2, 1983.
- [9] KELL, G. S. -Density, Thermal Expansivity, and Compressibility of Liquid Water from 0°C to 150°C: Correlations and Tables for Atmospheric Pressure and Saturation, Reviewed and Expressed on the 1968 Temperature Scale, J. Chem. Eng. Data, 20(1), 1975.
- [10] LEADBETTER, A. J. -The Thermodynamic and Vibrational properties of H₂O and D₂O Ice, Proc. Roy. Soc., A287, 1965.
- [11] MIRON V, COSTIUC L., COSTIUC I. -Valorificarea resurselor energetice recuperabile de potenţial termic scăzut în scopuri energetice. Analele Universităţii din Galaţi, Fascicula IV, 1996-1997, p.37-43, ISSN 1221-4558.

[12] TURTOI G., COSTIUC L., BENDREA C. -Modelarea extractiei cu fluide supracritice: Aspecte termodinamice, Lucrările Sesiunii de Comunicări Științifice ale Universității “Aurel Vlaicu”, Arad, Ed.a IV-a, “25 ani de Învățământ tehnic superior aradean”, vol.V, 1997, ISBN 973-98365-5-0.