

MODIFIED CLAUS PROCESS APPLIED TO NATURAL GAS FOR SULFUR RECOVERY

Nicușor Vatachi

”Dunărea de Jos” University of Galați

ABSTRACT

Approximately 25% of the natural gas being brought into production from new sources requires H_2S removal and disposal. Consequently, sulfur removal processes will play an increasingly larger role in future gas processing. As late as 1950, over half of the world sulfur supply came from “voluntary producers,” that is, companies whose principal purpose was to produce elemental sulfur. Now, these producers furnish less than 5% of the world’s supply and “involuntary producers,” primarily petroleum refineries and natural gas plants, are the major source of the element. The most common method of converting H_2S into elemental sulfur, is the Claus process or one of its modifications. Unfortunately, the exit stream from Claus plants usually cannot meet environmental emission requirements, and, consequently, a tail gas cleanup unit (TGCU) is often employed to eliminate the last of the sulfur compounds. The most commonly used processes are Shell Claus off Gas Treating (SCOT), SUPERCLAUS, and cold-bed adsorption (CBA). This paper describes Claus and tail gas cleanup processes.

REFERENCES

- [1] Clark, P., et al., “Enhancing the Performance of the CBA Process by Optimizing Catalyst Macro porosity”, Proceedings of the Laurance Reid Gas Conditioning Conference, Norman, 2002, 79.
- [2] d’Haêne, P.E., “Tail Gas Treating”, Proceedings of the Laurance Reid Gas Conditioning Conference, Norman, 2003, 89.
- [3] *Engineering Data Book*, 12th ed., Sec. 22, Sulfur Recovery, Gas Processors Supply Association, Tulsa, 2004.
- [4] Hyne, J.B., “The sulfur bubble”, *Hydrocarbon Eng.*, 10 (4) 23, 2005.
- [5] Johnson, J.E. and Hatcher, N.A., “A comparison of established sulfur degassing technologies”, Proceedings of the Laurance Reid Gas Conditioning Conference, Norman, 2003, 131.
- [6] Kohl, A. L. and Nielsen, R.B., “*Gas Purification*”, Gulf Publishing, Houston, TX, 1997.
- [7] Leppin, D., “Large-scale sulfur recovery”, *Gas TIPS*, 26, 2001.
- [8] Oberding, W., et al., “Lessons Learned and Technology Improvements at the Lost Cabin Gas Plant”, Proceedings of the Laurance Reid Gas Conditioning Conference, Norman, 2004, 273.
- [9] Parnell, D., “Look at Claus unit design”, *Hydrocarbon Process.*, 64 (9) 114, 1985.
- [10] Strickland, J.F., et al., “Relative capabilities and costs of tail gas clean-up processes”, *Gas TIPS*, 7 9, 2001.